

MAINTENANCE AND CLEANING USING JOHNSON WAX PROFESSIONAL / JOHNSON DIVERSEY

Clear Anodized Finish

CAUTION!!!

- Always use "WET FLOOR" signs and/or caution tape when performing any wet maintenance.
- Always refer to MSDS for use of PPE (Proper Protective Equipment)
- Floor Finish and Floor Strippers are **NOT** recommended on this floor.
- **DO NOT** use High Alkaline products on Alumafloor Products
- **DO NOT** use Blue, Black or Brown Pads on Alumafloor Products
- See manufacturer's instructions for other restrictions and additional information

Daily Maintenance

Sweep and/or dust mop the floor daily to remove surface dirt and unwanted particles from scratching the flooring surface.

Damp mop or autoscrub using Johnson Wax Professional Stride Neutral Cleaner. Dilute products as recommended on label, use *red* pad only if using autoscrubber or 175-rpm single-disc machine.

Note: If Disinfectant is needed, use Virex II 256 at recommended dilution rates.

Deep Cleaning Procedure

1. Sweep and/or dust mop the floor daily to remove surface dirt and unwanted particles from scratching the flooring surface.
2. Thoroughly scrub using Stride Neutral Cleaner. Dilute products as recommended on label, use *red* pad only. This can be done with a 175-rpm swing machine or autoscrubber.
3. **DO NOT** use blue, black or brown pads
4. Pick up soiled solution with wet/dry vac or auto scrubber.
5. Rinse floor thoroughly and allow to dry completely.

**FOR MORE INFORMATION PLEASE CONTACT:
JohnsonDiversey Technical Support: (800) 558-2332**